

TECHNICAL DATA SHEET



Bouni® 4221
Version 2.0 @CN

Reversion Date: 06/19/2020
Print Date: 07/10/2020

Chemical nature

Ethylene maleic anhydride copolymers

Benefits

- Promote adhesion to various substrates
- Effective dispersing agent of pigments and fillers
- Release agent

Delivery Specifications/*General Properties

Characteristics	Unit	Value	Test Method
Drop Point	[°C]	120~126	GB/T 4507-2014
Viscosity @140°C	[mPa·s]	80~120	GB/T 2794-2013
Density	[g/cm ³]	0.97	GB/T 1033.2-2010
Acid Number	[mgKOH/g]	16~20	GB/T 4945-2002
Grafting Rate	[%]	3	Titration
Appearance	-	Fine grain	-

Packaging/Storage

Products are packaged in net weight 20 kg compound bags and shipped on pallets, 40 bags to a pallet. Please store in a dry area at normal ambient temperatures. Minimum shelf life is 2 years from the date of shipping when properly stored.

Safety

The product does not require a hazard warning label.

For further information please refer to the Material Safety Data Sheet(MSDS).

Contact

www.bouni-wax.com

DaRong Center, No.180 Haier Road, QingDao City, 266101

TEL: +86-532-55760890

FAX: +86-532-55760890

Disclaimer: The information submitted in this publication is based on our current knowledge and experience. In view of the many factors that may affect processing and application, these data do not relieve processors of the responsibility of carrying out their own tests and experiments; neither do they imply any legally binding assurance of suitability for a specific purpose. It is the responsibility of those to whom we supply our products to ensure that any proprietary rights and existing laws and legislation are observed.

END OF TECHNICAL DATA SHEET

® Registered trademark of Bouni.

© 2020 QingDao Bouni Chemical Co.,Ltd.